



CARGO-FORCE® —Cable Ties



Cable Ties is made of UL-approved Nylon 66, 94V-2 material. The products are resistant to heat, acid, erosion, ageing and have good insulation & strong endurance.

Cable ties are a secure, convenient and inexpensive way to handle your wire management.

Product Features

*Smooth, rounded edges do not cut insulation - or hands - and are comfortable to work with.

*Closely spaced positive-locking teeth allow fine adjustment to tie bundles of all sizes.

*No metal parts; head and pawl are integrally molded for added strength and durability.

*Self-locking, one-piece, low-profile head conserves space.

*V-shaped raised ridges on bent tip give a sure grip and easy pull-up.

*All RT Series cable ties have a bent tip for easier pickup, insertion and pull-up.



Working Temperature: -35°C to 85°C

Color: Natural (White, standard color), UV black, and other colors are available as request.


Packing: Polybag 100pcs or 1000pcs

Application:

widely used to pack TV, PC, complete bicycle, fix inner circuit of household appliances, lamps, electric engine, electronic toys, machinery and equipment, oil pipelines, ship cable lines; it also can be used in Agriculture, gardening, handicrafts, supermarket, park fast, good insulation, self-lock, easy to use



Specification



Model	Length		Width mm	Tie Scope-E mm	Bearing	
	Inch	mm			lbs	kg
Miniature Cable Ties						
Ideal for light duty bundling applications not to exceed 18 lbs. of bundling force. Available in a wide range of colors, including fluorescent colors. Also available in Halar & Tefzel Fluoropolymer for environmentally sensitive applications.						
QT-80M-G	3.2"	80	2.5	2-16	18	8
QT-100M-G	4"	100	2.5	2-22		
QT-120M-G	4.7"	120	2.5	2-30		
QT-150M-G	6"	150	2.5	2-35		
QT-200M-G	8"	200	2.5	3-50		
Intermediate Cable Ties						
Intermediate duty bundling applications not to exceed 40 lbs. of bundling force. Wrap, tension and cut (optional) to remove excess tail.						
QT-150I-G	6"	150	3.6	3-35	40	18
QT-180I-G	7.1"	180	3.6	3-42		
QT-200I-G	8"	200	3.6	3-50		
QT-250I-G	10"	250	3.6	3-65		
QT-280I-G	11"	280	3.6	3-70		
QT-300I-G	12"	300	3.6	3-80		
Standard Cable Ties						
Standard duty bundling applications not to exceed 50 lbs. of bundling force						
QT-120S-G	4.7"	120	4.5	3-30	50	22
QT-150S-G	6"	150	4.5	3-35		
QT-180S-G	7.1"	180	4.5	3-42		
QT-200S-G	8"	200	4.7	3-50		
QT-250S-G	10"	250	4.7	3-65		
QT-300S-G	12"	300	4.7	3-80		
QT-350S-G	14"	350	4.8	3-90		
QT-380S-G	15"	380	4.8	3-102		
QT-400S-G	16"	400	4.8	3-105		
QT-450S-G	18"	450	4.8	3-110		
QT-500S-G	20"	500	4.8	3-150		



Heavy Duty Cable Ties

Heavy duty bundling applications not to exceed 120 lbs. of bundling force. Wrap, tension and cut (optional) to remove excess tail.

QT-150LH-G	6"	150	7.2	3-35	120	55
QT-200LH-G	8"	200	7.2	3-50		
QT-250LH-G	10"	250	7.2	4-65		
QT-300LH-G	12"	300	7.2	4-80		
QT-350LH-G	14"	350	7.2	4-90		
QT-380LH-G	15"	380	7.2	4-100		
QT-400LH-G	16"	400	7.2	4-105		
QT-450LH-G	18"	450	7.2	4-110		
QT-500LH-G	20"	500	7.2	4-150		

Extra Heavy Duty Cable Ties

Extra-heavy duty bundling applications not to exceed 175 lbs. of bundling force. Wrap, tension and cut (optional) to remove excess tail.

QT-400H-G	16"	400	9.0	8-105	175	80
QT-450H-G	18"	450	9.0	8-118		
QT-500H-G	20"	500	9.0	8-150		
QT-550H-G	21.6"	550	9.0	8-160		
QT-600H-G	23.6"	600	9.0	8-170		
QT-650H-G	25.6"	650	9.0	8-185		
QT-720H-G	28.3"	720	9.0	10-195		
QT-800H-G	31.5"	800	9.0	10-230		
QT-900H-G	35.5"	900	9.0	10-265		

Contact us



United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,
Minhang District, Shanghai, China

TEL: 86-21-34634180

FAX: 86-21-34625293

Web: www.cargo-protec.com.cn

Mail: info@united-ports.com