



CARGO MOVE


——Lifting Points



Lifting Points, quality grade 80, compact, light structure, with ball bearing, may be charged on all sides, turning 360° , link's rotation radius max 180° . It satisfies lifting in different directions, and overcomes the shortcoming of dangerous side-lifting in domestic market.

Product Features

- *Bearing in all direction.
- *Rotatable with vertical bearing.
- *Easy installation, only need screw hole.
- *100% electromagnetism crack measuring bolts, Bolts strength grade: 8.8/12.9
- *CORRUD-DT surface treatment, antiseptic effect is 20 times higher than common galvanization surface.
- *Meets EN 1677-4 standard.
- *Red coat surface, galvanization treatment.



Specification

Model	Load (kg)	Oval Link (mm)	Size B(mm)	Size C(mm)	Size G(mm)	Size E(mm)	Size H(mm)	Size A(mm)
09500010	300	55×30	36	15	M8	13	51	41
09500030	450	55×30	36	15	M10	18	51	41
09500050	500	55×30	36	15	M12	18	51	41
09500125	1120	55×30	36	15	M16	20	54	43
09500200	2000	70×34	49.5	19	M20	30	68	56
09500300	3150	85×40	57	22	M24	30	78	64
09500500	5300	85×40	66	23.5	M30	35	98	82

Contact us



United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,
Minhang District, Shanghai, China
TEL: 86-21-34634180
FAX: 86-21-34625293
Web: www.cargo-protec.com.cn
Mail: info@united-ports.com