



**UNITED-PORTS**  
One Call, Total Delivery

## CARGO-LIFT

### —Trolley Clamp



**Trolley Clamp** is designed lightly, easy to operate. It can be fixed on overhead beams for the transportation of the objects and materials. Working with the hoisting hook matched, it facilitates carrying and moving equipment.

Yale trolley clamp is an international brand with quality assurance.

### YALE Trolley Clamp—Model CTP

#### Product Features:

- \*Load Range: 1000Kg-3000Kg
- \*Easy fixing on overhead beams for the attachment and transport of loads.
- \*Central threaded spindle provides quick adjustment to the required beam width.
- \*Locking lever secures the adjustment,



#### Specification

| Model   | Capacity (kg) | Beam Flange Width (mm) | Min. Curve Radius (mm) | Weight (kg) |
|---------|---------------|------------------------|------------------------|-------------|
| CTPA 1T | 1000          | 60~150                 | 0.6                    | 2.5         |
| CTP 2-A | 2000          | 75~200                 | 0.9                    | 9.9         |
| CTP 2-B | 2000          | 200~300                | 0.9                    | 10.3        |
| CTP 3-A | 3000          | 75~200                 | 1.15                   | 17.5        |
| CTP 3-B | 3000          | 200~300                | 1.15                   | 19.5        |

### KONECRANES Trolley Clamp—Model KPT

#### Product Features

- \*Load Range: 250Kg-10000Kg
- \*Various of hoisting hooks can be matched with KPT
- \*Trolley Width can be adjusted by the measured size
- \*It can manual pushing, or use heavy-duty chains and wheels
- \*Trolley flange is made of high resistivity steel materials





**UNITED-PORTS**  
One Call, Total Delivery

\*Rolling: the shape is designed for running in all types of single-track steel

\*Hanger Shaft: It's made of steel materials to ensure the entire structure firm, and can adjust the width of lanes in order to adapt to all kinds of different specifications of the guide tracks (Different width can be adjusted by KPT style)

### Specification

| Model        | Capacity (kg) | Beam Flange Width (mm) |
|--------------|---------------|------------------------|
| KPT-250-202  | 250           | 50-202                 |
| KPT-500-200  | 500           | 50-200                 |
| KT-500-310   | 500           | 188-310                |
| KPT-1000-200 | 1000          | 65-200                 |
| KPT-1000-310 | 1000          | 200-310                |
| KPT-2000-200 | 2000          | 88-200                 |
| KPT-2000-310 | 2000          | 188-310                |

### Contact us



#### United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,  
Minhang District, Shanghai, China  
TEL: 86-21-34634180  
FAX: 86-21-34625293  
Web: [www.cargo-protec.com.cn](http://www.cargo-protec.com.cn)  
Mail: [info@united-ports.com](mailto:info@united-ports.com)