

CARGO-LIFT

-Vertical Plate Lifting Clamp



Vertical Plate Lifting Clamp is used in single or one pair for vertical lifting of steel plate. The max lifting weight of single clamp is called rated capacity. It can only lift one piece of plate each time. Multi-Plates lifting is prohibited. Collision shall be avoided during lifting. When lifting, the locking handle must be turned upward to make the spring tense. When unloading, it should be turned downward. The clamp and plate can be separated only after spring loosing.

Product Features

* Suitable for the lifting, 180° turning and vertical transfer of steel plates and constructions.

* Fitted with a locking device.

*Fitted with a hinged hoisting eye movable in all directions, enable the user to place and lift the load from any direction.

*Fitted with special hook device, easy installation in horizontal position.

*New design of clamp, with great technical improvement comparing with the traditional version.

*New model clamp with a wider jaw caliber, lifting plates in various thickness.

*Conforms to Europe CE Safety Standard.

Product Display



Specifications

Model	Rated Capacity (t)	Suitable Thickness of Plate(mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	K (mm)
CL05	0.5	0-15	0-17	44	128	212	30	103	36	35	10
CL10	1	0-20	0-22	63	167	295	48	138	50	51	12
CL20	2	0-25	0-27	76	202	370	70	164	52	56	16
CL30	3	0-30	0-32	85	237	418	75	193	78	59	20







Contact us



United-Ports (Shanghai) LTD.

Add:No.3293, South Hongmei Rd, Minhang District,Shanghai,China TEL:86-21-34634180 FAX:86-21-34625293 Web: <u>www.cargo-protec.com.cn</u> Mail: <u>info@united-ports.com</u>