



CARGO-MOVE

— Webbing Sling



Webbing Sling has different types. Divided by materials: anti-acid sling, anti-alkali sling, high-strength sling; Divided by use: traction sling, lifting sling.

Product Features

- *Each 25mm sling width adds, 1T pulling force increases;
- *Wide bearing surface decreases the load pressure on the surface, light and flexible, easy to use in narrow space;
- *There will no damage to the objects when lifting smooth and precise goods;
- *Non-conductive, non-electrolyte;
- *Produced based on European Standard EN1492-1, made of polyester fiber,
- *Material: polyester, polypropylene, cotton dacron, surface with polyurethane Resin sizing treatment, strong and durable;
- *CE&JIS certified;
- *Breaking force: 1: 7
- *No knot-using
- *Working temperature range: -40°C~100°C;
- *Extensibility: 2%-5% under the ultimate working force



Specification

Model	Capacity (kg)	Length (m)	Width (mm)	Inclination Angle		Fit 7° 2.0	Inclination Angle of one end fixed	
				45°— 60° 1.0	7°—45° 1.4		45°— 60° 0.8	7°—45° 0.8
Purple Yale								
HBD-01000(1T-1M)	1000	1	30	1000	1400	2000	800	1120
HBD-01000(1.5M)	1000	1.5	30	1000	1400	2000	800	1120
HBD-01000(1T-2M)	1000	2	30	1000	1400	2000	800	1120
HBD-01000(2.5M)	1000	2.5	30	1000	1400	2000	800	1120
HBD-01000(1T-3M)	1000	3	30	1000	1400	2000	800	1120
HBD-01000(3.5M)	1000	3.5	30	1000	1400	2000	800	1120
HBD-01000(1T-4M)	1000	4	30	1000	1400	2000	800	1120



HBD-01000(1T-5M)	1000	5	30	1000	1400	2000	800	1120
HBD-01000(5.5M)	1000	5.5	30	1000	1400	2000	800	1120
HBD-01000(1T-6M)	1000	6	30	1000	1400	2000	800	1120
HBD-01000(1T-8M)	1000	8	30	1000	1400	2000	800	1120
Purple DOLECO								
1t,1m	1000	1	30	1000	1400	2000	800	1120
1t,3m	1000	3	30	1000	1400	2000	800	1120
1t,5m	1000	5	30	1000	1400	2000	800	1120

Model	Capacity (kg)	Length (m)	Width (mm)	Inclination Angle		Fit 7° 2.0	Inclination Angle of one end fixed	
				45°— 60° 1.0	7°—45° 1.4		45°— 60° 0.8	7°—45° 0.8
Green Yale								
HBD-02000(2T-1M)	2000	1	60	2000	2800	4000	1600	2240
HBD-02000(1.5M)	2000	1.5	60	2000	2800	4000	1600	2240
HBD-02000(2T-2M)	2000	2	60	2000	2800	4000	1600	2240
HBD-02000(2.5M)	2000	2.5	60	2000	2800	4000	1600	2240
HBD-02000(2T-3M)	2000	3	60	2000	2800	4000	1600	2240
HBD-02000(3.5M)	2000	3.5	60	2000	2800	4000	1600	2240
HBD-02000(2T-4M)	2000	4	60	2000	2800	4000	1600	2240
HBD-02000(4.5M)	2000	4.5	60	2000	2800	4000	1600	2240
HBD-02000(2T-5M)	2000	5	60	2000	2800	4000	1600	2240
HBD-02000(2T-6M)	2000	6	60	2000	2800	4000	1600	2240
HBD-02000(2T-8M)	2000	8	60	2000	2800	4000	1600	2240
Green DOLECO								
2t,2m	2000	2	60	2000	2800	4000	1600	2240
2t,2m	2000	3	60	2000	2800	4000	1600	2240
2t,5m	2000	5	60	2000	2800	4000	1600	2240

Model	Capacity (kg)	Length (m)	Width (mm)	Inclination Angle		Fit 7° 2.0	Inclination Angle of one end fixed	
				45°— 60° 1.0	7°—45° 1.4		45°— 60° 0.8	7°—45° 0.8
Yellow Yale								
HBD-03000(3T-1M)	3000	1	90	3000	4200	6000	2400	3360
HBD-03000(1.5M)	3000	1.5	90	3000	4200	6000	2400	3360
HBD-03000(3T-2M)	3000	2	90	3000	4200	6000	2400	3360
HBD-03000(2.5M)	3000	2.5	90	3000	4200	6000	2400	3360
HBD-02000(3T-3M)	3000	3	90	3000	4200	6000	2400	3360
HBD-03000(3.5M)	3000	3.5	90	3000	4200	6000	2400	3360



HBD-03000(3T-4M)	3000	4	90	3000	4200	6000	2400	3360
HBD-03000(3T-5M)	3000	5	90	3000	4200	6000	2400	3360
HBD-03000(3T-6M)	3000	6	90	3000	4200	6000	2400	3360
HBD-03000(3T-8M)	3000	8	90	3000	4200	6000	2400	3360
Yellow DOLECO								
3t,2m	3000	2	90	3000	4200	6000	2400	3360
3t,3m	3000	3	90	3000	4200	6000	2400	3360
3t,5m	3000	5	90	3000	4200	6000	2400	3360

Model	Capacity (kg)	Length (m)	Width (mm)	Inclination Angle		Fit 7° 2.0	Inclination Angle of one end fixed	
				45°— 60° 1.0	7°—45° 1.4		45°— 60° 0.8	7°—45° 0.8
Gray Yale								
HBD-04000(4T-1M)	4000	1	120	4000	5600	8000	3200	4480
HBD-04000(1.5M)	4000	1.5	120	4000	5600	8000	3200	4480
HBD-04000(4T-2M)	4000	2	120	4000	5600	8000	3200	4480
HBD-04000(2.5M)	4000	2.5	120	4000	5600	8000	3200	4480
HBD-04000(4T-3M)	4000	3	120	4000	5600	8000	3200	4480
HBD-04000(3.5M)	4000	3.5	120	4000	5600	8000	3200	4480
HBD-04000(4T-4M)	4000	4	120	4000	5600	8000	3200	4480
HBD-04000(4T-5M)	4000	5	120	4000	5600	8000	3200	4480
HBD-04000(4T-6M)	4000	6	120	4000	5600	8000	3200	4480
HBD-04000(4T-8M)	4000	8	120	4000	5600	8000	3200	4480

Model	Capacity (kg)	Length (m)	Width (mm)	Inclination Angle		Fit 7° 2.0	Inclination Angle of one end fixed	
				45°— 60° 1.0	7°—45° 1.4		45°— 60° 0.8	7°—45° 0.8
Red Yale								
HBD-05000(1.5M)	5000	1.5	150	5000	7000	10000	4000	5600
HBD-05000(5T-2M)	5000	2	150	5000	7000	10000	4000	5600
HBD-05000(2.5M)	5000	2.5	150	5000	7000	10000	4000	5600
HBD-05000(5T-3M)	5000	3	150	5000	7000	10000	4000	5600
HBD-05000(3.5M)	5000	3.5	150	5000	7000	10000	4000	5600
HBD-05000(5T-4M)	5000	4	150	5000	7000	10000	4000	5600
HBD-05000(5T-5M)	5000	5	150	5000	7000	10000	4000	5600
HBD-05000(5T-6M)	5000	6	150	5000	7000	10000	4000	5600
HBD-05000(5T-8M)	5000	8	150	5000	7000	10000	4000	5600



UNITED-PORTS
One Call, Total Delivery

Contact us



UNITED-PORTS
One Call, Total Delivery

United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,
Minhang District, Shanghai, China

TEL: 86-21-34634180

FAX: 86-21-34625293

Web: www.cargo-protec.com.cn

Mail: info@united-ports.com