



CARGO-LIFT
—Wire Rope Slings



Wire Rope Slings is divided into **Pressed Wire Rope Slings** and **Spliced Wire Rope Slings**, used for slinging and dragging. It is made of Grade 1770 oil-free galvanized steel wire rope in accordance with European Standard EN13414, , 5-fold safety factor, can be used in range of -40 °to 100 °,

Product Features

- *Standard wire rope slings equipped with aluminum alloy pressing sleeve;
- *Steel pressing sleeve is recommended to use in high temperature or serious abrasion;
- *Standard cylindrical pressing;
- *Spliced sling is very flexible, easy to pull out from goods' bottom, other slings may be locked;
- *Pay attention to not bend the aluminum pressing sleeve;
- *CE certified.



Aluminum Pressing Sleeve

Product Display



Pressed Wire Rope Slings



Spliced Wire Rope Slings

Specification

Model	Type	Operating Load (kg)	Diameter of Rope (mm)	Length of Lifting Ring (mm)	Usable Length (mm)
0213140102	Pressed Wire Rope Slings	2000	14	210	2
0213160102	Pressed Wire Rope Slings	2700	16	240	2
0213180102	Pressed Wire Rope Slings	3150	18	270	2
0213200102	Pressed Wire Rope Slings	4000	20	300	2



UNITED-PORTS
One Call, Total Delivery

0213220102	Pressed Wire Rope Slings	5000	22	330	2
0213240102	Pressed Wire Rope Slings	6300	24	360	2
0213260102	Pressed Wire Rope Slings	7000	26	390	2
0213280102	Pressed Wire Rope Slings	8000	28	420	2
0253140102	Spliced Wire Rope Slings	1700	14	210	2
0253160102	Spliced Wire Rope Slings	2200	16	240	2
0253180102	Spliced Wire Rope Slings	2800	18	270	2
0253200102	Spliced Wire Rope Slings	3400	20	300	2
0253220102	Spliced Wire Rope Slings	4200	22	330	2
0253240102	Spliced Wire Rope Slings	5000	24	360	2
0253260102	Spliced Wire Rope Slings	5800	26	390	2
0253280102	Spliced Wire Rope Slings	6700	28	420	2

Contact us



UNITED-PORTS
One Call, Total Delivery

United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,
Minhang District, Shanghai, China

TEL: 86-21-34634180

FAX: 86-21-34625293

Web: www.cargo-protec.com.cn

Mail: info@united-ports.com