



**CARGO-MOVE**  
—Hand Pallet Truck



**Noble-lift AC Series**

- \*Comfortable A-type plastic handle bar;
- \* Polyurethane and nylon caster is optional; Polyurethane caster has lower noise and longer service time
- \*Integral sealed oil pump, key parts made in Germany, oil leakage-proof;
- \*Chrome plated piston rod, durable structure, overload protection, descent speed control;
- \*Valve disk uses torsional unit for distinguishing scattered parts and maintenance.
- \*Meet EN1757-2 standard.



**Specification**

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load (kg)
AC	85	200	1150	540	160×50	Nylon double fork caster	2500
AC	85	200	1150	540	160×50	Polyurethane single fork caster	2500
AC	85	200	1220	685	160×50	Nylon double fork caster	2500
AC	85	200	1220	685	160×50	Nylon double fork caster	2500
AC	85	200	1220	685	160×50	Polyurethane single fork caster	2500
AC	85	200	1150	540	160×60	Nylon double fork caster	3000
AC	85	200	1150	540	160×60	Polyurethane single fork caster	3000
AC	85	200	1220	685	160×60	Nylon double fork caster	3000
AC	85	200	1220	685	160×60	Polyurethane single fork caster	3000



**Noble-lift DF Series**

- \*Hand descent control valve, adjustable in 3 locations;
- \*Adjustable handspike, arc front-end fork, easy cargo loading and unloading;
- \*"C" fork is durable for overload. All flexible parts are coated with long last lubricant.
- \*Meet EN1757-2 standard.



**Specification**

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load (kg)
DF	85	200	1150	540	160×60	Polyurethane single fork caster	2500
DF	85	200	1150	540	160×60	Nylon double fork caster	2500
DF	85	200	1220	685	160×60	Polyurethane single fork caster	2500
DF	85	200	1220	685	160×60	Nylon double fork caster	2500
DF	85	200	1150	540	160×60	Polyurethane single fork caster	3000
DF	85	200	1150	540	160×60	Nylon double fork castor	3000
DF	85	200	1220	685	160×60	Polyurethane single fork caster	3000
DF	85	200	1220	685	160×60	Nylon double fork caster	3000

**XILIN DF Series**

\*Main body of oil pump is welded by pre-build blocks. Rough chromed piston and plunger are for smooth operation and prevent overloading of oil pump & sealed components.

\*Safety valve prevents overweight.

\*Excellent 180° rotation device.



**Specification**

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load (kg)
DF	85	200	1150	520	160×45	Nylon double fork caster	2500
DF	85	200	1220	685	160×45	Polyurethane single fork caster	2500



### XILIN BF Series

- \* Purely mechanical system, tight junction between steer and pump cover, easy replacement of rear wheel;
- \* Grease device in all key points ensures pallet truck's long service time and easy control.
- \* Decrease rate and over-load bypass is particularly controlled for truck's more durable using.
- \*Reliable oil leakage-proof power system.



### Specification

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load (kg)
BF	85	200	1150	520	160×45	Nylon double fork caster	2500
BF	85	200	1220	685	160×45	Polyurethane single fork caster	2500

### XILIN NF Series

- \* Inner overflow valve is for overload protection, avoiding overload and reducing maintenance fee.
- \* Movable parts is matched with alloy bushing to absorb uneven loading, abrasion resistant, long service time and easy replacement.



### Specification

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load (kg)
NF	85	195	1150	520	160×45	Nylon double fork caster	2500
NF	85	195	1220	685	160×45	Polyurethane single fork caster	2500



### Linde Series:

\*The tiller head is wrapped with rubber boot. Lifting, descending and middle moving is controlled by handle bar. Steering wheel angle:  $\pm 110^\circ$ .

\* Frame and airframe: high twisting-proof channel steel structure, available in bearing any cargo, easy fork entering and existing shielded pallet.

\*Hydraulic lifting system: M20 series lifting system and its components are installed in a hard chill casting seal cavity for convenience maintenance. Deterioration prevention and overload protection is realized by overflow valve. Automatic descending governor valve ensures cargo descending stably. All components can be replaced separately, maintained easily. Double sealing ring structure highly improves the service life of hydraulic oil pump. The using hydraulic oil can work in range of  $-20^\circ\text{C} \sim +40^\circ\text{C}$ .



**M20-530**

### Specification

Model	Fork Min. Height (mm)	Fork Max. Height (mm)	Fork Length (mm)	Fork Width (mm)	Fork Size (mm)	Caster Type	Rated Load(kg)
M20-530	85	205	1150	530	150×52	Polyurethane single fork caster	2000
M20-685	85	205	1150	685	150×52	Polyurethane single fork caster	2000
M25-530	85	205	1150	530	150×52	Polyurethane single fork caster	2500
M25-685	85	205	1150	685	150×52	Polyurethane single fork castor	2500
M30-540	85	205	1150	540	150×52	Polyurethane single fork caster	3000
M30-680	85	205	1150	685	150×52	Polyurethane single fork caster	3000

### Contact us



#### United-Ports (Shanghai) LTD.

Add: No. 3293, South Hongmei Rd,  
Minhang District, Shanghai, China

TEL: 86-21-34634180

FAX: 86-21-34625293

Web: [www.cargo-prottec.com.cn](http://www.cargo-prottec.com.cn)

Mail: [info@united-ports.com](mailto:info@united-ports.com)