

Steel Cable Seals *Seal-Force®*
Specification & Price List



DH-K



DH-K2



DH-K3



DH-K4



DH-K5



DH-K6

| Type | Applications | Material | Features | Printing | Color | Package | Carton Size (cm) | Weight/CTN (kg) | FOB Price (USD) |
|-------|---|---|---|--|-----------------------------|--------------------------|--------------------------------------|---------------------------------|-----------------|
| DH-K | Doors, trucks, tanker, rail carriages, containers | Low carbon steel, wrapped with ABS, Braided aircraft cable construction | 1.8mm diameter cable with standard (total) length of 230mm, length available; Petroleum & Sunlight resistant; Self-locking mechanism; tensile strength: $\geq 300\text{kgf}$; Removable by bolt cutters. | Thermal stamping or laser printing, Company logo or name, sequential number, (most 7 No.); the height of letter and No. $\leq 4\text{mm}$ | red/yellow/white/blue/green | 100pcs/bag 10bags/ctn | 32.5X21X21.5cm (12.8" X 8.3" X 8.5") | G/W: 17.5 kg ; N/W: 16.5 kg; | *** |
| DH-K2 | Doors, trucks, tanker, rail carriages, containers | Zinc extrusion wrapped with ABS; Braided aircraft cable construction | 1.8mm diameter cable with standard (total) length of 228mm, length available; Petroleum & Sunlight resistant; Self-locking mechanism; tensile strength: $\geq 300\text{kgf}$; Removable by bolt cutters. | Thermal stamping or laser printing, Company logo or name, sequential number, (most 7 No.s); the height of letter and No. $\leq 4\text{mm}$ | red/yellow/white/blue/green | 100pcs/bag 10bags/ctn | 32.5X21X21.5cm (12.8" X 8.3" X 8.5") | G/W: 17.5 kg ; N/W: 16.5 kg; | *** |

| | | | | | | | | | |
|-------|---|--|---|--|-----------------------------|--------------------------|---|--------------------------------|-----|
| DH-K3 | Doors, trucks, tanker, rail carriages, containers | Zinc extrusion wrapped with ABS;Braided aircraft cable construction | 1.8mm diameter cable with standard (total) length of 210mm, length available;Petroleum & Sunlight resistant;Self-locking mechanism;tensile strength: 300kgf;Removable by bolt cutters. | Thermal stamping or laser printing, Company logo or name, sequential number, (at most 6 No.s); | red/yellow/white/blue/green | 20pcs/bag 25bags/ctn | 32.5X 21X 21.5cm (12.8" X 8.3" X 8.5") | G/W: 13.5 kg; N/W: 12.5 kg; | *** |
| DH-K4 | Doors, trucks, tanker, rail carriages, containers | Zinc extrusion, free of plastic;Braided aircraft cable construction | 1.8mm diameter cable with standard (total) length of 210mm, length available;Petroleum & Sunlight resistant;Self-locking mechanism;tensile strength: ≥ 300kgf;Removable by bolt cutters. | Thermal stamping or laser printing, Company logo or name, sequential number, (most 6 No.); | red/yellow/white/blue/green | 100pcs/bag 10bags/ctn | 32.5cm X 21cm X 21.5cm (12.8" X 8.3" X 8.5") | G/W: 28.5 kg; N/W: 27.5 kg; | *** |
| DH-K5 | Doors, trucks, tanker, rail carriages, containers | Lock body is aluminium alloy;Braided aircraft cable construction | 0.5mm diameter cable with standard (total) length of 210mm, length available;Petroleum & Sunlight resistant;Self-locking mechanism;tensile strength: ≥ 1900kgf;Removable by bolt cutters. | Thermal stamping or laser printing,Company logo or/and name, sequential number, (most 6 No.s); the height of letter and No. ≤4mm | red/yellow/white/blue/green | 100pcs/bag 10bags/ctn | 39X25X15cm (15.35" X 9.85" X 5.9") | G/W: 16 kg; N/W: 15 kg; | *** |
| DH-K6 | Doors, trucks, tanker, rail carriages, containers | Low carbon steel, wrapped with ABS,Braided aircraft cable construction | 0.5mm diameter cable with standard (total) length of 345mm, length available;Petroleum & Sunlight resistant;Self-locking mechanism;tensile strength: ≥ 1000kgf;Removable by bolt cutters. | Thermal stamping or laser printing, Company logo or name, sequential number, (most 7 No.s); | red/yellow/white/blue/green | 250pcs/ctn | 40X 20X25cm (15.75" X 7.87" X 9.85") | G/W: 16 kg ; N/T: 15 kg | *** |

United-Ports Brand Cargo Force®

Remarks:for the detailed price,please contact us by emailing to info@united-ports.com