

**Auto Range Digital Multimeter  
Specification & Price List**



Specification & Model		UT803	
		Auto Range Digital Multimeter	
DC voltage	Range	600mV/6V/60V/600V/1000V	
	Precision	±(0.3%+1)	
AC Voltage	Range	600mV/6V/60V/600V/1000V	
	Precision	±(0.5%+2)	
DC Current	Range	600μA/6mA/60mA/600mA/10A	
	Precision	±(0.5%+1)	
AC Current	Range	600μA/6mA/60mA/600mA/10A	
	Precision	±(0.8%+2)	
Resistance	Range	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ	
	Precision	±(0.5%+2)	
Capacitance	Range	6nF/60nF/600nF/6uF/60uF/600uF/6mF	
	Precision	±(2%+5)	
Frequency	Range	10Hz-60MHz	
	Precision	±(0.1%+3)	
Temperature	Range	40°C ~1000°C / -40°F ~1832°F	
	Precision	±(1%+3)/±(1.5%+5)	
LCD Size(mm)		128x28	
Max. Display/Color		5999/Red and Grey	
Weight(g)		2400	
Size(mm)		310x240x105	
Power		AC 220V±10%/50Hz or No.2 battery R14(1.5V × 6pcs)	
Standard accessories		Test Lead, AC220V Power Cord, English Manual, Point Contact, Temperature Probe, Alligator Clip, Multi-Purpose Socket, RS232C Interface Cable, USB Interface Cable, Software	
Other function		10A fuse, Diode test, Onoff warning, Audion test, Min/max mode data hold, RS232 interface, USB interface, Backlight display, All symbol display, Auto power off, Low volts display	
Export Price (USD/pc)		***	